

Installation Locations:

Indoor, outdoor & coastal locations, in residential, Commercial & industrial

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 500mm (86") Approximately 600mm (106")

Motor:

188mm x 35mm DC motor

Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Top Canopy & Downrod:

Materials: Steel

Available Colours:

White and Black

Blades

Sizes: 2220mm (86") / 2700mm (106") Materials: Aerodynamic Wedge Compression

Blade Pitch: 15°

Available Blade Colours:

White, Black and Natural Oak

Extra Information:

Introduced into the HPI range in 2019

6 Speed remote controller

Reversible

Airflow CMH:

86" - 35,480 on High speed (Speed 6) 106" - 43,620 on High speed (Speed 6)

Standard Canopy Cover:

Suitable for flat ceiling

Wall Controller Speed Capacitor Values:

N/A

Rotational Diameter:

2220mm (86") / 2700mm (106") blade sweep

Ceiling to top side of the blade:

Approximately 420mm (86") / 520mm (106")

Weight Including Packaging:

Complete fan: 18.7kg (86") / 19.1kg (106")

Packaging Dimensions (cm):

86" Motor pack: 53L x 34W x 31H

Blade inner box: 100.5L x 5.5W x 17.3H Blade outer box: 102L x 18.5W x 19.3H

106" Motor pack: 53L x 34W x 31H

Blade inner box: 122.5L x 5.5W x 16H Blade outer box: 127L x 18.5W x 18H

Accessories (Supplied separately):

Extension Threaded Down Rod 60mm diameter

240V DC Wall Control

Warranty:

2 years in-home warranty on all electric components (control modules, remote control system, lighting and accessory wall control)

3 years standard "in home" warranty

3 years extended warranty on motor only (excluding labour)

Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
61	76	90	96	112	120
12.5	21.5	31	38	62	75
Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
48	59	67	73	85	97
13	20	30	37	61	75
	61 12.5 Speed 1 48	61 76 12.5 21.5 Speed 1 Speed 2 48 59	61 76 90 12.5 21.5 31 Speed 1 Speed 2 Speed 3 48 59 67	61 76 90 96 12.5 21.5 31 38 Speed 1 Speed 2 Speed 3 Speed 4 48 59 67 73	61 76 90 96 112 12.5 21.5 31 38 62 Speed 1 Speed 2 Speed 3 Speed 4 Speed 5 48 59 67 73 85